

## Air Filter Regulator

Material Code	Sl.No.	Description			
	1	Service	Instrument air		
	2	Max Inlet Pressure	6 kg/cm2		
	3	Enclousre	Weather proof		
	4	Outlet pressure Range	0 - 4 kg/cm2		
	5	End Connection	1 inlet ,1 outlet and 1 pressure guage port		
	6	Bowl Capicity	130 cc		
	7	Ambinent Temperature	up to 80degree C		
	8	Adjustment knob with nut	Unbrakable plastic moulded on C.S. stem		
	9	Body Spring case and Filter Biowl	Die cast aluminium alloy		
	10	Filter	Sintered bronze		
	11	Main Valve	Neoprene		
	12	Drain Valve	Brass		
	13	Diaphragm	Nylon reinforced Neoprene		
	14	Main Spring	SS 316		
	15	Body Spring case and Filter Biowl	Die cast aluminium alloy		
	16	Mounting	Surface or Panel		
	17	Acessories	Provided with guage (Range: 0-8Kg/cm2)		
	18	Make	Placka,Shavo Norgen,Fairchild		
700-034-301-233	19	Size	Inlet Size	Outlet Size	Quantity
700-034-301-232			1/4"(NPT)	1/4" (NPT)	25 40
			1/2" (NPT)	1/2" (NPT)	20 30

