

PR no. / / dt:

Annexure – 1

Supply of Check valve/ NRV for vacuum pump hot water transfer &amp; recirculation purpose with the following specifications::

Sl. No.	Material code	Material Description & Size	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Quantity required
1	300 024 091 593	<b>VALVE TYPE:</b> Check valve/ NRV Swing Type <b>SIZE:</b> 02", Class: #150 <b>FLANGES ENDS:</b> As Per ANSI B 16.5 Class 150, Flat Face <b>SERVICE:</b> Hot Water <b>Rate of Valve:</b> PN 1.0 <b>Ph:</b> 6.5- 7.5 <b>BODY:</b> Cast : ASTM A 216 GR WCB <b>COVER:</b> Bolted ASTM A 216 GR WCB <b>DISC:</b> SWING TYPE : 13% Cr STEEL FACING/13% Cr Steel <b>DOOR :</b> CAST IRON (IS:210 FG 200) <b>BODY SEAT RING:</b> 13% CR, SS Type 410 <b>DOOR SEAT RING:</b> 13% CR, SS Type 410 <b>COVER GASKETS:</b> SP. WND. 304 WITH GRAFOIL FILTER <b>HINGE PIN:</b> SS TYPE 316 (No Casting) <b>FASTENERS:</b> ASTM A 194 GR 2H, Flow Direction Required.	01	5				15
2	300 024 091 757	-----Do----- for check valve of Size: 4"	01	10				25
3	300 024 091 867	-----Do----- for check valve of Size: 6"	01	10				20

Make: BDK/ MICROFINISH / KSB / L&amp;T / LEVCON / AQUAFLOW / FLOWTECH / KHIMJI / Prime


